

# Premium Floor Finish

Premium Floor Finish

## Description

Premium Floor Finish sets a new standard of performance for floor finish products. With a superior gloss and high anti-slip rating, Premium Floor Finish offers excellent abrasion resistance, durability and long-term clarity. An extra high solids formula, Premium Floor Finish extends stripping cycles from 18 to 24 months outlasting traditional finish products.

## Features and Benefits

- Works on most hard floor surfaces including: terrazzo, marble, vinyl, , concrete, , terracotta, , etc. Not recommended for outdoor use. Designed for high traffic areas.
- Excellent for prestige floors and all busy floors, including shopping centres, hospitals and commercial buildings.
- High anti-slip rating typically above - 0.70 (Industry Standard 0.40). Increased safety and reduces risk of public liability claims.
- Extra high solids resulting in maximum durability. Requires fewer coats saving time and labour.
- High gloss, ultra-durable, ultra-high speed finish. Excellent presentation and response to UHS burnishing.
- Scuff, scratch and abrasion resistant.
- Repels dirt and soil, staying clean and bright for longer.
- Rapid dry time.
- Increased coverage. Covers more square meters of floor space coverage of up to 60 sq. meters per litre.

## Product Specifications & Information

Appearance:	Off-White Emulsion
pH	8.0 – 9.5
Viscosity, cps	<100
% Solids	25-26% w/w
Dry Time:	Allow at least 30 minutes depending on weather conditions
Coverage:	55-60m <sup>2</sup> /L
Slip Rating	0.70 (Industry Standard 0.40)

### **Use Directions**

Prior to application of Premium Floor Finish, floors must be adequately stripped with Multistrip, rinsed thoroughly and allowed to completely dry.

### ***Initial Application***

Apply 2-3 thin coats. Allow floors to thoroughly dry between coats and prior to burnishing. DO NOT apply more than 4 coats in a 24 hour period.

Optional for old porous floors and heavy traffic areas: Apply 2 thin coats of Premium Floor Sealer, then apply 3-4 coats of Premium Floor Finish.

### ***Maintenance***

For a floor that has been deep cleaned or scrubbed, allow to dry thoroughly. Apply 1-2 thin coats. Allow floor to dry thoroughly between coats and prior to burnishing.

### ***Buffing and Burnishing***

Premium Floor Finish is ideal for use in no-buff or buffing programs using all speeds of buffing or burnishing machines. For spray buffing, mop-on or auto-scrubber restoring use in conjunction with Gloss, Restore & Maintain.

### **Storage**

This product should be stored under cover, out of direct sunlight and avoiding extreme temperature changes.

### **Safety Information**

Classified as NON-HAZARDOUS according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) criteria of Safe Work Australia and is classified as a NON-DANGEROUS GOOD according to the Australian Dangerous Goods Code. Refer to our product safety data sheet (SDS) for more information or consult your Chemform representative for further assistance.

### **Packages**

3 x 5L